

**Mot-g 0.37 230/400 50 27r SK01 71L/4 B3 1011**

Article number: 90-00-3749

**Dimensions**

Length	369.00 mm
Width	198.00 mm
Height	176.00 mm
Actual weight	13.465 kg

Basic data

Running mode	S2 + Xmin	S1-S10
Betriebsart S2 Minuten	60 min	
Motor size	71	
Gear type	Spur gear	
Gear design	Foot version	
Gear position	M1	M1-M6
Menge Getriebeöl	0.22 kg	
Norm	IEC60034	
Weight	14 kg	

Rated values

Phases	3 Anzahl
Frequency	50 Hz
Pole pair	4
Type of connection	Star/Delta
Permiss. ambient temp. during operation	-20 - 40 °C
Kabel Motor	4 adrig

**Classification**

Wirkungsgradklasse	IE1 IE1- IE5
IP protection rating	IP55 IP
Insulation class	F
Certifications	CE

Dimensions

Output shaft length	40 Länge
---------------------	----------

Rated values 50 Hz

Nominal power	0,44 kW
Nominal voltage delta connection	230 V
Nominal voltage star connection	400 V
Current consumption delta connection	2,11 A
Current consumption star connection	1,22 A
Anlaufstrom I_a/I_n	3.2 Faktor
Power factor	0.74
Motor speed	1345 r/min
Nominal torque motor	3,12 Nm
Gear speed	26 r/min
Nennmoment Getriebe [Volllast]	159 Nm
Service factor	0.6 Fs