

**Mot-g 0,37 230/400 50 17,9r SK20-71L/4 V6**

Article number: 90-00-3805

**Dimensions**

Length	399.00 mm
Width	187.00 mm
Height	231.00 mm
Actual weight	18.800 kg

Basic data

Running mode	S2 Minuten	S1-S10
Betriebsart S2 Minuten	60 min/%	
Design electric motor	V6	
Motor size	71	
Gear type	Spur gear	
Gear design	Foot version	
Gear position	M2	M1-M6
Menge Getriebeöl	1 kg	
Norm	IEC60034	
Weight	19 kg	

Rated values

Phases	3 Anzahl
Frequency	50 Hz
Type of connection	Star/Delta
Permiss. ambient temp. during operation	-10 - 40 °C
Kabel Motor	4 adrig

**Classification**

Wirkungsgradklasse	IE1 IE1- IE5
IP protection rating	IP55 IP
Insulation class	F
Certifications	CE

Dimensions

Output shaft length	60 Länge mm
---------------------	----------------

Rated values 50 Hz

Nominal power	0,44 kW
Nominal voltage delta connection	230 V
Nominal voltage star connection	400 V
Current consumption delta connection	2,11 A
Current consumption star connection	1,22 A
Power factor	0.74
Motor speed	1345 r/min
Gear speed	18 r/min
Nennmoment Getriebe [Vollast]	239 Nm
Service factor	0.8 Fs