

**Fan FF056-6ET 1x230V 50/60Hz 1.9/2.8A f/tube**

Article number: 60-47-9058

**Dimensions**

Length	545.00 mm
Width	530.00 mm
Height	216.00 mm
Actual weight	13.305 kg

Basic data

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation in pipe
Chimney	560 - BD 580

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50/60 Hz
Control	Frequency converter (with all-pole sinusoidal filter) / Transformer / Triac

Classification

IP protection rating	IP54
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E15

Rated values 50 Hz

Elektrische Nennleistung	0.4 kW
www.bigdutchman.shop	11/3/2023

**Rated values 50 Hz**

Nominal voltage single-phase	230 V
Nominal current single-phase	1,9 A
Speed	920 U/min
Ambient temperature	-25 - 45 °C
Sound power level L _w	74 dB
Sound pressure level L _p	49 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	10254 m ³ /h
Characteristic curve – 10 Pa	9824 m ³ /h
Characteristic curve – 20 Pa	9411 m ³ /h
Characteristic curve – 30 Pa	8826 m ³ /h
Characteristic curve – 40 Pa	8089 m ³ /h

Spec. power 50 Hz

Characteristic curve – 0 Pa	33.5 W/(1000m ³ /h)
Characteristic curve – 10 Pa	37.5 W/(1000m ³ /h)
Characteristic curve – 20 Pa	41.2 W/(1000m ³ /h)
Characteristic curve – 30 Pa	45.1 W/(1000m ³ /h)
Characteristic curve – 40 Pa	50.2 W/(1000m ³ /h)

Rated values 60 Hz

Elektrische Nennleistung	0.62 kW
Nominal voltage single-phase	230 V
Nominal current single-phase	2,8 A
Speed	1000 U/min
Ambient temperature	-25 - 45 °C